



FEATURES

- With the push of a button, the unit displays a green or red light, indicating good water quality or service required, respectively.
- Tests for TDS or conductivity levels.
- Eight programmable set points (by dip switch).
- Bright LED lights.
- Simple to use.
- Factory Calibrated to 100 ppm NaCl. Re-calibration is unnecessary.
- Comes equipped with Mur-lok® Quick-Connect T-fitting (1/4 inch standard, also available in 3/8" or 1/2").
- Excellent Reverse Osmosis (RO) or Deionization (DI) monitor
- Installs quickly and easily.



If the TDS level is above the set-point, the red light will illuminate, indicated service is required. If the TDS level of the product water is below the set-point, the green light will indicate the filter is good.

SPECIFICATIONS

- TDS/EC Range: 0-5000 ppm (10,000 μ S)
- Max. Set Point: 50 ppm (100 μ S)
- Accuracy: \pm 3%
- ATC: No
- Cable Length: 24.5" (including sensor)
- Fittings: 1/4"
- Power source: 4 x 1.5V button cell batteries (included)
- Battery life: Approx. one year
- Size: 7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in.)
- Weight: 39.7 g (1.4 oz.) (not including sensor)

Distributed by:

**APPLIED
MEMBRANES INC.**

2325 Cousteau Ct., Vista, CA 92081-8346

(760) 727-3711 • Fax: (760) 727-4427

<http://www.appliedmembranes.com>

sales@appliedmembranes.com

1 YEAR WARRANTY