



Ideal for any water filtration system, including reverse osmosis systems, coolers and much more.



Use the monitor to determine when a filter need to be changed.

## FEATURES

- Displays TDS level of a single water line.
- Highly efficient and accurate due to its advanced microprocessor technology.
- Auto-Off function conserves battery power. The unit shuts off automatically after 10 minutes of non-use.
- Wide Range 0-9990 ppm (From 0 - 999 ppm the resolution is 1 ppm. From 1000 to 9990 ppm, the resolution is 10 ppm, indicated by a blinking 'x10' image.)
- Factory Calibrated: our meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated with a mini-screwdriver.
- Comes equipped with Mur-lok® Quick-Connect T-fitting (1/4 inch standard, also available in 3/8" or 1/2" ).
- Installs quickly and easily.

## SPECIFICATIONS

- Range: 0-9990 ppm
- Accuracy:  $\pm 2\%$
- Conversion Factor: NaCl (avg. 0.5)
- Cable Length: 24.5" (including sensor)
- Fittings: 1/4" standard, also available with 3/8" or 1/2"
- Power source: 2 x 1.5V button cell batteries (included)
- Battery life: approx. 1000 hours of continuous use
- Size: 7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in.)
- Weight: 79.4 g (2.8 oz.)

Distributed by:

**APPLIED  
MEMBRANES INC.**

2325 Cousteau Ct., Vista, CA 92081-8346

(760) 727-3711 • Fax: (760) 727-4427

<http://www.appliedmembranes.com>

[sales@appliedmembranes.com](mailto:sales@appliedmembranes.com)

**1 YEAR WARRANTY**