

DM2: INDUSTRIAL DUAL TDS METER



FEATURES

- Highly efficient and accurate due to its advanced microprocessor technology.
 - Displays TDS levels of the Feed Water and Product Water with in & out electrode probes.
 - Auto-Off function conserves battery power. The unit shuts off automatically after 20 seconds.
 - Dual Range - Measures from 0-999 ppm, with a resolution of 1 ppm. From 1000 to 9990 ppm, the resolution is in 10 ppm increments, indicated by a blinking 'x10' image.
 - Factory Calibrated.
 - Comes equipped with 1/4 inch John Guest Quick-Connect T-fittings as shown. Also available with 3/8" fittings.
 - Installs quickly and easily.
- Differences from the DM-1:**
- Designed for commercial/industrial applications.
 - Stronger, water-resistant casing.
 - Improved design, including an extra large, easy-to-read LCD display.
 - Longer, waterproof, shielded cables.
 - Variable mounting bracket.

Measure the tap water coming in vs. the purified water going out of your system at any time.

Use the meter to determine when the filters need to be changed.

Install the meter for your customers so they'll always know how their system is performing.

Install on industrial systems such as car washes, manufacturing, and food processing.

SPECIFICATIONS

- Range: 0-9990 ppm
- Accuracy: $\pm 2\%$
- Cable Length: 46" (including sensor)
- Power source: 2 AAA batteries (included)
- Battery life: over 1000 hours of continuous use
- Size: 11.6 x 6.8 x 1.8 cm (4.6 x 2.6 x .7in.)
- Weight: 201.3 g (7.1 oz.)

**THREE YEAR
WARRANTY**

Distributed By:

**APPLIED
MEMBRANES INC.®**

2325 Cousteau Ct., Vista, CA 92081 · (760) 727-3711 · FAX (760) 727-4427
<http://www.appliedmembranes.com> · sales@appliedmembranes.com