

Product Data Sheet

H-F2520AC

20" Carbon Block Filter Cartridge

Performance Specifications		
Function:	Chlorine, taste, color, and odor reduction	
Capacity:	35,000 gallon Chlorine Reduction @ 2 GPM	
Flow Rate:	2 GPM (7.5 LPM)	
Micron Rating:	10 μ	
Initial ΔP :	<2.0 psid @ 2 GPM	

Physical Characteristics:	
Carbon Type:	Coconut Shell Carbon
Nominal Size:	20" Standard (Fits 20" Standard Filter Housing)
Dimensions:	2.87" O.D. × 1.25" I.D. × 20"L
End Caps:	Polypropylene End Caps with Compression Gaskets
AMI H-F2520AC filters have been designed to fit most 20" Standard filter housings.	

Operating Conditions:

Temperature:	40° - 100°F (4.5° - 37.7°C)
Max. Operating Pressure:	125 psig (8.6 bar)

- All information provided is based on data believed to be reliable. It should be used for evaluation and verification but not as a warranty.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Activated carbon block filters are not designed to remove bacteria or viruses.
- Actual performance results may vary based on the level of organic contaminants in the influent water, changes in pH and upon other conditions that may be encountered during actual use.

General Installation/Operation/Maintenance Requirements

- Flush new cartridge for 10 minutes prior to use.
- Replace cartridge when rated capacity is reached, or when flow becomes too slow.
- Install in compliance with state and local laws and regulations.

Applied Membranes, Inc. assumes no liability for results obtained or damages incurred through the improper application of the above information and data.



© 2012 Applied Membranes, Inc. All Rights Reserved. Specifications subject to change without notice.