

LG Water Solutions

Data Sheet



Brackish Water Reverse Osmosis (RO) Membranes

LG BW 400 R Dura

Highly durable membranes



Overview


LG Chem's $NanoH_2O^{TM}$ brackish water RO membranes serve various municipal and industrial applications and have been operating in the major utilities around the world. LG BWRO membranes, all incorporated with innovative Thin Film Nanocomposite (TFN) technology, are offered in industry standard configurations and can easily fit into existing and new RO plants.

LG BW R (High Rejection) membranes offer a combination of high rejection, reliability, and durability; suitable for high salinity brackish water and wastewater reuse applications.

Product Specifications

Active Membrane	Permeate flow rate, GPD (m³/d)	Stabilized Salt	Minimum Salt	Feed Spacer,
Area, ft² (m²)		Rejection, %	Rejection, %	mil
400 (37)	10,500 (39.7)	99.6	99.5	34

Test Conditions: 2,000 ppm NaCl at 25°C (77°F), 225 psi (15.5 bar), pH 7, Recovery 15%. Permeate flows for individual elements may vary +/-15%.



A	B [O.D.]	C [I.D.]	Weight
mm (in.)	mm (in.)	mm (in.)	kg (lbs.)
1,016	200	28.6	16
(40)	(7.9)	(1.125)	(35)

Operating Specifications

<u> </u>	
Max. Applied pressure	600 psi (41 bar)
Max. Chlorine concentration	< 0.1 ppm
Max. Operating temperature	45°C (113°F)
pH Range, Continuous (Cleaning)	2-11 (1-13)
Max. Feedwater turbidity	1.0 NTU
Max. Feedwater SDI (15 mins)	5.0
Max. Feed flow	75 gpm (17 m ³ /h)
Max. Pressure drop (ΔP) for each element	15 psi (1.0 bar)

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. LG Chem assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. NanoH₂O is the Trademark of The LG Water Solutions or an affiliated company of LG Chem. All rights reserved. © LG Chem. Ltd.



