

## QC-1: QUICK CHECK TDS/CONDUCTIVITY MONITOR

HM Digital QC-1: Press the "Push-to-Check" button for an instant water quality check. If the TDS level is above the set-point, the red light will illuminate, indicated service is required. If the TDS level of the product water is below the set-point, the green light will indicate the filter is good.

## **FEATURES**

- With the push of a button, the unit displays a green or red light, indicating good water quality or service required, respectively.
- Tests for TDS or conductivity levels.
- Eight programmable set points (by dip switch).
- Bright LED lights.
- Simple to use.
- Factory Calibrated to 100 ppm NaCl. Re-calibration is unnecessary.
- Excellent Reverse Osmosis (RO) or Deionization (DI) monitor
- Installs quickly and easily.

## **SPECIFICATIONS**

TDS/EC Range: 0-5000 ppm (10,000  $\mu$ S) Max. Set Point: 50 ppm (100  $\mu$ S)

Accuracy: ±3%

ATC: No

Cable Length: 24.5" (including sensor)

Fittings: 1/4"

Power source: 4 x 1.5V button cell batteries (389-A) (included)

**Size:** 7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in.)

Weight: 39.7 g (1.4 oz.) (not including sensor))









Requires tee fitting (sold separately) with 1/4" QC Connection for installation.

Distributed By:



2450 Business Park Drive, Vista, CA 92081, USA (760) 727-3711 • FAX: (760) 727-4427

Internet: <a href="www.appliedmembranes.com">www.appliedmembranes.com</a>
E-mail: <a href="mailto:sales@appliedmembranes.com">sales@appliedmembranes.com</a>







